

# instructions

## Japanese Wireless Data Card



### Installation (Apple Macintosh, OS X)

You may load the software for this device before you travel or whilst in Japan. Please note, the data card will not operate unless you are in Japan.

### Step 1 – to be completed before or after arrival in Japan

- a. **Do not insert card until you have completed step 1.**
- b. Close all applications.
- c. Insert the installation CD-Rom into your Mac to download the driver. If the software does not auto run please access it by double clicking on the folder.
- d. You will now see two folders (“CCL for PC card” and “CCL for CS card”). Copy the CCL files from the PC card folder to the following route directory on your Mac - MAC HARD DRIVE / LIBRARY / MODEM SCRIPTS.
- e. Reboot your machine (the data card can only be recognised after your Mac is rebooted).

### Step 2 – to be completed in Japan only

- a. Insert the data card into your Mac.
- b. Turn on your Mac and go to the Apple Menu and click the “System Preference” icon.

- c. Within the “System Preference” menu, click on the “Network” icon. When the “the new port was detected” message appears, click “OK”.
- d. You can now select the connection as “pc card-modem-port”.
- e. This setting will produce a pop up menu, click the “PPP” tab.
- f. You are then asked for some details as follows:
  - password: bmobile
  - access point number: 0570570138##64  
(note: using this number will give you a “multi-link” connection on a 128kbps channel. If you require a “single link” connection use the same number but with ##61 at the end).
- g. In the “PPP” option, un-tick the box “Sending a PPP echo packet”.
- h. Click the “Modem” tab and ensure that “Honda-Elc BMH10-J” is selected as the model of PC card modem in the pop-up menu.
- i. To finish, click “Apply now”.

### Step 3 – to activate your connection

- a. Click on the small modem icon that appears on the top menu (near the clock).
- b. To disconnect simply click on this icon again.

### Step 4 – optional e-mail booster

- a. Save and close all applications.
- b. In the main Apple menu go to “System preferences” and click “Network”.
- c. Click on the “Proxies” tab.
- d. Tick the “web” box and enter the following details:
  - address: michelle.bmobile.ne.jp
  - port: 32080
- e. Click “Apply now” to complete the booster set up.